



GEWINDESTÖPSEL MIT  
 DEM FLANSCH

DIN 910

festigkeitsklasse  
 5.8

| d   | c | D  | e     | i  | m  | s  |
|-----|---|----|-------|----|----|----|
| M10 | 3 | 14 | 10,89 | 8  | 6  | 10 |
| M12 | 3 | 17 | 14,20 | 12 | 6  | 13 |
| M14 | 3 | 19 | 14,20 | 12 | 6  | 13 |
| M16 | 3 | 21 | 18,72 | 12 | 6  | 17 |
| M18 | 4 | 23 | 18,72 | 12 | 8  | 17 |
| M20 | 4 | 25 | 20,88 | 14 | 8  | 19 |
| M22 | 4 | 27 | 20,88 | 14 | 8  | 19 |
| M24 | 4 | 29 | 23,91 | 14 | 9  | 22 |
| M26 | 4 | 31 | 26,17 | 16 | 10 | 24 |
| M27 | 4 | 32 | 26,17 | 16 | 10 | 24 |
| M30 | 4 | 36 | 26,17 | 16 | 10 | 24 |
| M33 | 5 | 39 | 29,56 | 16 | 11 | 27 |
| M36 | 5 | 42 | 29,56 | 16 | 11 | 27 |
| M38 | 5 | 44 | 29,56 | 16 | 11 | 27 |
| M39 | 5 | 46 | 29,56 | 16 | 11 | 27 |
| M42 | 5 | 49 | 32,95 | 16 | 12 | 30 |
| M45 | 5 | 52 | 32,95 | 16 | 12 | 30 |