



SWORZEŃ Z ŁBEM I
CZOPEM GWINTOWYM

PN-90/M-83007
DIN 1445

kl. właściwości mechanicznych:
5.6, 5.8, 8.8, 10.9, 12.9

d	M6	M8	M10	M12	M12	M12	M16	M16	M20	M20	M24	M24	M27	M30	M33	M36
dz	8	10	12	14	16	18	20	22	24	27	30	33	36	40	45	50
D	14	18	20	22	25	28	30	33	36	40	44	47	50	55	60	66
S	11	13	16	18	21	24	27	30	32	36	36	41	46	50	55	60
k	3	4	4	4	4,5	5	5	5,5	6	6	8	8	8	8	9	9
b	11	14	17	20	20	20	25	25	30	30	36	36	39	42	45	50
l																
16																
18																
20																
22																
24																
26																
28																
30																
32																
35																
40																
45																
50																
55																
60																
65																
70																
75																
80																
85																
90																
95																



HSW-Fabryka Elementów Złącznych
FASTEC Sp. z o.o.
 ul. Lubelska 41, 37-470 Zaklików
 tel.:(0-15) 8738822, fax:(0-15) 8738325
 e-mail: info@fastec.pl



ISO 9001

d	M6	M8	M10	M12	M12	M12	M16	M16	M20	M20	M24	M24	M27	M30	M33	M36
dz	8	10	12	14	16	18	20	22	24	27	30	33	36	40	45	50
D	14	18	20	22	25	28	30	33	36	40	44	47	50	55	60	66
S	11	13	16	18	21	24	27	30	32	36	36	41	46	50	55	60
k	3	4	4	4	4,5	5	5	5,5	6	6	8	8	8	8	9	9
b	11	14	17	20	20	20	25	25	30	30	36	36	39	42	45	50
l																
100																
120																
140																
160																
180																
200																